

**WHAT IS CLAIMED IS:**

1. A method for segmenting an object within a current digital image frame, comprising the steps of:
  - receiving a set of control points used in deriving an object boundary from a prior image frame, wherein the received set of control points serves as an initial set of control points for the current digital image frame;
  - defining a restricted area within the current digital image frame based on the received set of control points, wherein the restricted area corresponds to a band about the object boundary;
  - updating the initial set of control points to an updated set of control points in response to an operator command;
  - defining a current-frame object boundary for said object of the current digital image frame using the updated set of control points, wherein said step of defining the current-frame object boundary comprises deriving a closed contour connecting each control point of the updated set of control points, wherein only image data within the restricted area are eligible to form the closed contour.
2. The method of claim 1, wherein the step of updating comprises updating the initial set of control points to an updated set of control points in response to an operator command to perform either one of moving a control point or adding a control point.
3. The method of claim 2, further comprising the step of:
  - when the operator command either one of moves or adds a select control point outside the restricted area, redefining the restricted area to encompass the select control point.
4. The method of claim 1, further comprising, prior to the step of updating, the steps of:
  - deriving edge energy data for the current image frame; and
  - deriving and displaying an initial estimate of the current-frame object boundary based on the received set of control points and the derived edge energy data.

5. The method of claim 4, wherein the current digital image frame is displayed and the initial estimate of the current-frame object boundary is overlaid onto the current digital image frame with the initial set of control points frame, wherein the step of updating the initial set of control points comprises selecting a control point of the initial set of control points with a pointing device and dragging the selected control point to a new location.

6. The method of claim 5, further comprising the steps of:  
testing the new location of the selected control point to determine whether the selected control point is outside the restricted area;  
when the new location of the selected control point is outside the restricted area, redefining the restricted area to encompass the selected control point in the new location.

7. The method of claim 5, wherein the step of defining the current-frame object boundary comprises deriving a path from the selected control point to a first adjacent control point and deriving a path from the selected control point to a second adjacent control point.

8. The method of claim 1, wherein the step of deriving a closed contour comprises for each one control point of the updated set of control points deriving a path from said each one control point to an adjacent control point, wherein the step of deriving a path comprises:

determining a distance from said one control point to said adjacent control point;

when said distance is less than a threshold distance applying a first set of rules for deriving the path from said one control point to the adjacent control point;

when said distance is greater than the threshold distance applying a second set of rules, different from the first set of rules, for deriving the path from said one control point to the adjacent control point.

9. The method of claim 8, wherein the first set of rules provide a more accurate path than the second set of rules for connecting control points which are less than the threshold distance apart.

10. The method of claim 8, wherein the second set of rules provide a more accurate path than the first set of rules for connecting control points which are more than the threshold distance apart.

5 11. The method of claim 1, wherein the step of defining the restricted area, comprises morphologically dilating a contour connecting the received set of control points.

10 12. The method of claim 1, further comprising the step of receiving an object boundary estimate of a prior digital image frame and wherein the step of defining the restricted area, comprises defining the restricted area within the current digital image frame from the received object boundary estimate, including the received set of control points.

15 13. An apparatus for segmenting an object within a current digital image frame, comprising:

a display for displaying the current digital image frame;

20 means for overlaying a set of control points used in deriving an object boundary from a prior image frame, wherein the overlaid set of control points serves as an initial set of control points for the current digital image frame;

a first processor which derives a restricted area within the current digital image frame based on the initial set of control points, wherein the restricted area corresponds to a band encompassing the initial set of control points;

25 an input device by which an operator is able to change the initial set of control points, the changed set of control points being an updated set of control points;

30 a second processor which generates a current-frame object boundary for said object of the current digital image frame using the updated set of control points by deriving a closed contour connecting each control point of the updated set of control points, wherein only image data within the restricted area are eligible to form the closed contour.

14. The apparatus of claim 13, wherein in response to the operator either moving or adding a select control point outside the restricted area with the input device, said first processor redefines the restricted area to encompass the select control point.

15. The apparatus of claim 13, wherein the first processor comprises means for testing the new location of the selected control point to determine whether the selected control point is outside the restricted area, the first processor redefining the restricted area to encompass the selected control point in the new location when the new location of the selected control point is outside the restricted area.

16. The apparatus of claim 13, wherein the second processor comprises means for deriving a path from a selected control point to a first adjacent control point and deriving a path from the selected control point to a second adjacent control point, wherein the selected control point has a location changed by the operator.

17. The apparatus of claim 16, wherein the deriving means comprises:  
means for determining a distance from said selected control point to said first adjacent control point;

when said distance is less than a threshold distance applying a first set of rules for deriving the path from said selected control point to the first adjacent control point;

when said distance is greater than the threshold distance applying a second set of rules, different from the first set of rules, for deriving the path from said selected control point to the first adjacent control point.

18. The apparatus of claim 17, wherein the first set of rules provide a more accurate path, than the second set of rules, for connecting control points which are less than the threshold distance apart.

19. The apparatus of claim 17, wherein the second set of rules provide a more accurate path, than the first set of rules, for connecting control points which are more than the threshold distance apart.

20. The apparatus of claim 13, wherein the first processor comprises means for morphologically dilating a contour formed by the initial set of control points to define the restricted area.

21. The apparatus of claim 20, wherein said contour is an object boundary estimate from a prior digital image frame that includes the initial set of control points.

22. The apparatus of claim 13, wherein the first processor and the second processor are a common processor.

23. The apparatus of claim 13, further comprising:

means for deriving edge energy data for the current digital image frame;

means for deriving an initial estimate of the current-frame object boundary based on the received set of control points and the derived edge energy data, wherein said initial estimate of the current-frame object boundary is overlaid onto the current digital image frame.

5

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995